

Ninja ZX-10R

± 8,913 *



Model Year 2009

COLOURS



Ebony



Lime Green



Pearl Stardust White

FEATURES



Race-ready engine



Hybrid instrument cluster



Revised RAM air



Exhaust system

SPECIFICATIONS

Engine type	Liquid-cooled, 4-stroke In-Line Four
Displacement	998 cm ³
Bore x stroke	76.0 x 55.0 mm
Compression ratio	12.9:1
Valve/Induction system	DOHC, 16 valves
Maximum power	138.3 kW {188 PS} / 12,500 rpm
Maximum power with RAM Air	147.1 kW {200 PS} / 12,500 rpm
Maximum torque	113 N•m {11.5 kgf•m} / 8,700 rpm
Fuel system	Fuel injection: ø43 mm x 4 (Keihin) with oval sub-throttles, dual injection
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, wet sump with oil cooler
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Backbone/Twin-tube, aluminium (Pressed/die-cast composite structure)
Rake/Trail	25.5° / 110 mm
Suspension, front	43 mm inverted fork with DLC coating, rebound and compression damping, spring preload adjustability and top-out springs
Suspension, rear	Bottom-Link Uni-Trak with gas-charged shock and top-out spring. Stepless, dual-range (high/low-speed) Compression damping. Stepless Rebound damping. Fully adjustable Spring preload
Wheel travel, front	120 mm
Wheel travel, rear	125 mm
Tyre, front	120/70ZR17M/C (58W)
Tyre, rear	190/55ZR17M/C (75W)
Brakes, front	Dual semi-floating 310 mm petal discs, 10-button aluminium rotor carrier Dual radial-mount, opposed 4-(aluminium) piston
Brakes, rear	Single 220 mm petal disc Single-bore pin-slide, aluminium piston
Steering angle, left / right	27° / 27°
Dimensions (L x W x H)	2,110 mm x 710 mm x 1,135 mm
Wheelbase	1,415 mm
Ground Clearance	125 mm
Seat height	830 mm
Fuel capacity	17 litres
Curb Mass	208 kg
Automatic Headlights On (AHO)	n/a
Complies to EU emission limit	EURO 3

* Prices are recommended and inclusive of VAT @ 15% and on the road charges.