

Z1000

kawasaki's philosophy in a word

± 6,447 / ± 6,809 (ABS) *



Model Year 2009

COLOURS



Ebony



Candy Burnt Orange/Metallic Diablo Black



Pearl Crystal White/Atomic Silver

FEATURES



Subframe



Engine



Silencer



Fuel tank

SPECIFICATIONS

Engine type	Liquid-cooled, 4-stroke In-Line 4
Displacement	953 cm ³
Bore x stroke	77.2 x 50.9 mm
Compression ratio	11.2:1
Valve/Induction system	DOHC, 16 valves
Maximum power	92 kW {125 PS} / 10,000 rpm
Maximum torque	98.7 N·m {10.1 kgf·m} / 8,200 rpm
Fuel system	Fuel injection: ø36 mm x 4 (Keihin) with oval sub-throttles
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, wet sump
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Tubular backbone (with engine sub-frame), high-tensile steel
Rake/Trail	24.5° / 103 mm
Suspension, front	41 mm inverted fork with stepless rebound damping and spring preload adjustability
Suspension, rear	Bottom-Link Uni-Trak with gas-charged shock, stepless rebound damping and spring preload adjustability
Wheel travel, front	120 mm
Wheel travel, rear	150 mm
Tyre, front	120/70ZR17M/C (58W)
Tyre, rear	190/50ZR17M/C (73W)
Brakes, front	Dual semi-floating 300 mm petal discs
Brakes, rear	Single 250 mm petal disc
Steering angle, left / right	31° / 31°
Dimensions (L x W x H)	2,090 mm x 780 mm x 1,065 mm
Wheelbase	1,445 mm
Ground Clearance	160 mm
Seat height	820 mm
Fuel capacity	18.5 litres
Curb Mass	228 kg / 232 kg (ABS)
Automatic Headlights On (AHO)	n/a
Complies to EU emission limit	EURO 3

* Prices are recommended and inclusive of VAT @ 15% and on the road charges.